

COVID-19 Update

Power Dynamics business functions are operating as normal. All orders and shipments will continue to be processed as usual as we are considered by the State of NJ and the Department of Defense (DOD) a critical supplier to the Defense and Medical industries.

New Representation

Power Dynamics is pleased to announce **Apogee Solutions Group** as Representatives for the **New England** territory. Please contact **Dan Murphy** at **978-758-0015** or **V. J. Ladd** at **781-929-4834** for your immediate PDI needs.

PDI Points of Interest

- Contact **Matt Marzocca** on the Customer Service team for all of your sales inquiries and general sales questions.
mmarzocca@powerdynamics.com
973-560-0019 x225
- Regional Sales Contacts
 West—Dave Budge
dbudge@powerdynamics.com
 North—Tom Kinney
tkinney@powerdynamics.com
 South East—Call PDI
sales@powerdynamics.com

Contact Us

145 Algonquin Parkway
Whippany, NJ 07981
(973) 560-0019
sales@powerdynamics.com
powerdynamics.com



Power Dynamics, Inc.

**Medical Grade EMI/RFI Filters**

Power Dynamics has the industries largest selection of EMI/RFI filters. Our options include panel & snap-in versions in addition to multi-function modules, 1 & 2 stage and 3 phase options, all for domestic, international & medical builds.

Contact our expert Engineering department to help guide you to the correct filter selection.

Crosses to

Corcom, Schaffner, Schurter, Qualtek and more.

Compression Contact Connectors for Mobile Battery & PCB Applications

Power Dynamics' low profile compression connectors can be used in a variety of applications including:

- Battery Packs
- Docking/Cradles
- Portable Medical
- Gaming Consoles
- Barcode Scanners
- PDA's
- Handheld Terminals
- Board to Board
- Pluggable Modules
- Mobile Devices

Each connector is made of hi-temp thermoplastic and has reliable Beryllium Copper Gold plated spring contacts.

With a variety of heights and contact angles, they are designed for rugged use and can withstand up to 5000 mating cycles.

Specifications:

Current Rating: up to 3A
Temp Rating: -40°C to 85°C
Contacts: 3, 4, 10
Mounting: Surface Mount
Height: 1.1mm to 6mm
Package: Tape and Reel

Competition includes **AVX, TE, Meritec & Molex**

Custom designs are welcome!

IN STOCK!
10088

7'6" Black, North American, SVT 18/3 105°C C13/5-15P
Competitive Pricing!

**Recent Quotes & Design Wins**

- OH – IEC Connector - Wire Harness
- CN – Power Cord - Industrial Equipment
- ID – Knobs - Music Equipment
- FL – EMI/RFI Filter - Fume Hoods
- MN – Battery Contact - Medical Pulse Monitor
- S. CA – EMI/RFI Filter - Ventilator
- S. CA – Data Jack - Medical Equipment

