

See us at

Del Mar Electronics & Design Show— S. California
May 6 & 7, 2015

EDS—Las Vegas
May 12, 13 & 14, 2015

New PDI Representation

TEXAS

PDI is pleased to announce **Barry Sales, Inc.** as PDI representatives for the N. Texas territory. Please contact Dan Barry at (972)234-0255 for your local opportunities.

FL, GA, AL, MD, VA

PDI is pleased to announce **Brandel-Stephens & Co.** as PDI representatives for the FL, GA, AL, MS, TN, MD & VA territories. Please contact Ed Toomey at (561)998-2790 for your local opportunities.

PDI Points of Interest

- Contact **Josh Norkin** to help with all of your customer service needs and sales inquiries (x225)
jnorkin@powerdynamics.com
- When online, click **eTasks** for real time inventory, specifications, pricing & order status

Power Dynamics, Inc.

145 Algonquin Parkway
Whippany, NJ 07981
(973) 560-0019
sales@powerdynamics.com
www.powerdynamics.com



Power Dynamics, Inc.

Power Entry Modules IEC60320



Power Dynamics has the industries largest selection of multi-function power entry modules and inlets/outlets. Options include on/off switches, fuses and voltage selectors for international builds, all in a compact design with current capabilities of up to 20 Amps.

We also offer a complimentary line of filtered EMI/RFI power entry modules.

BACK IN STOCK!
10088

7'6" Black, North American,
SVT 18/3 105°C C13/5-15P

Call for a quote!

NEW!

Unmated IP67 Rating! 2 Amps!



Cap-less Harsh Environment

Power Dynamics Harsh Environment Series 2 maintains **IP67** rating while unmated!

Power: 2 Amps, 175V
Locking Type: Bayonet
Contacts: 8
Wire Gauge: 24 AWG max
Terminal Type: Solder, PC

The connectors are highly resistant to UV rays, chemicals, and shock/vibration.

Available now!

Detailed specifications are available at
www.powerdynamics.com

NEW!

Harsh Environment 25 Amps!



Harsh Environment Series

Power Dynamics Harsh Environment connectors are designed for rugged outdoor applications including agriculture, medical & security.

Power: 20 Amps UL, 400V
25 Amps VDE
Signal: 3 Amps, 60V
Locking Type: Bayonet
Contacts: 8 (4S+3P+E)
Terminal Type: Crimp

The connectors are **IP68/IPX9K** waterproof/pressure/steam rated and are highly resistant to UV rays, chemicals, and shock/vibration.

Detailed specifications are available at
www.powerdynamics.com

Recent Quotes & Design Wins

Colorado - EMI/RFI Filter - Instrumentation
Arizona - NEMA - Gaming Equipment
Pennsylvania - Power Cord - Medical Equipment
S. California - EMI/RFI Filter— Laboratory Equipment
Oregon - IEC Connector - Laboratory Equipment
N. Carolina - IEC Connector - Security
Minnesota - IEC Connector - Sensor Equipment

